



GBFIX RP

جي بي فيكس آر بي

Acrylic Based, Ready for use Mortar for fixing ceramic, porcelain and natural stones; including marble and granite, for Indoor and Outdoor applications.

Added Value

GBFix RP is a product specially designed for use with tiles, ceramics and modern porcelain; with very low absorption rate; which causes the separation of tiles over time from the walls and floors after installation, **GBFix RP** is acrylic based which is suitable for indoor and out door applications.

Application and Rates

- **GBFix RP** is ready for use from can, and it is creamy mortar applied by notched trowel, for all applications of ceramic, porcelain and all types of natural stones applications.
- Supplied in 20 kg plastic cans with inner, and sealed plastic bags.

Product Specifications

- White to off white creamy paste
- Application rate is 6-8 squared meters for the package taking into account the use of trowels 6 mm.
- Adhesion strength 1.5 N / mm².
- The pack will be suitable for use after 7 days of the first opening.
- Material density : 1.7 kg / L
- Application Rate 6-8 m² / 20 Kg. Pack .
- Product validity for one year from the date of production conditioned by the safe packaging.



Features:

GBFix RP is an adhesive mortar based on Acrylic resins for ceramics, porcelain and natural stones of all types with high adhesion strength, and fast drying properties, it is designed especially for porcelain, ceramic, natural stones and large tiles, non-porous ceramics that always de-bonding from walls and floors when fixed with regular mortar.

It is designed to provide adhesives for small and large slabs so that the material is placed on the walls before the tile is installed. Unlike the ordinary material, the mortar must be placed on the tile, making it difficult for the installation process, The use of **GBFix RP** also ensures that the tiles are not moved from their place after adhesion, especially in the walls. They also provide a strong fixation on the concrete and brick walls, which gives a longer life than regular mortar.



Application fields

GBFix RP could be used in the following places and areas:

- Fixing natural stones like marble and granite on floors or walls.
- Kitchens: Household and commercial, such as restaurants, Cafes and hotels.
- Super, hypermarkets and shopping malls.
- Bakeries and various manufacturing facilities.
- Fixing all types of tiles over wooden surfaces, or steel surfaces.
- To fix porcelain tiles and large ceramic tiles on the walls.
- **The product is not suitable for water submerged applications like swimming pools or water tanks.**
- Does not contain any harmful substances to the environment and water-based material which is not flammable, nor hazardous to the labors.

Components:

- Each package of **GBFix RP** contains the latest and special acrylic polymer which acts as a strong adhesive , in a special blend that makes the material easy to apply homogeneous and strong, glued to the walls, floors and the same item, no matter how low-absorbent ("very few pores") tiles, such as modern porcelain tiles.
- Each package also contains special additives to preserve the material working after months of storage, and special additive to make the material working after hours and days of can opening, without being subjected to loss the remaining material, or being dry.

Application Guide:

- * The surface must be cleaned from any dust.
- * The surface should be wetted specially in summer time with water, but standing water should be removed.
- GBFix RP** is applied by regular trowels and the material is trimmed with a notched trowels (as shown in the picture above).
- * The tiles must be well pressed against the material and the adhesive is firmly attached to the surface by hand-pressing or with a ceramic fixing hammer (Rubber Hammer).
- * If the tile is installed incorrectly, there is an opportunity to correct its position for 30 minutes without having to remove the material and re-add a new material as the material remains adjustable from 20-30 minutes after installation.



www.greenbuildegypt.com
info@greenbuildegypt.com
<https://www.facebook.com/GreenBuildEgypt>

Customer Service: 01050240446/ 01114544492
LandLine: 02-28607233
51 First Industrial Area Badr City, Cairo, Egypt.

